



## Scout® SPX Series

- · Large backlit display improves readability in low light conditions and is easier to view from a distance.
- · Integrated overload protection and impactresistant pan allow the balance to operate efficiently in demanding environments.
- Increase productivity with advanced weighing technology and stabilization time as fast as onesecond.









Totalization









RS232/ USB Interface

(Optional)



Battery

 $\overline{\mathbf{v}}$ Check-



Peak Hold





Display Hold

Ethernet

Interface (Optional)







Scout SPX Mole Weighing

Scout SPX Draftshield Revolve to Open

Scout Accessories						
OHAUS#	Description					
30268982	RS232 Interface Kit					
30268983	USB Host Interface Kit (for flash drive)					
30268984	USB Device Interface Kit (for PC)					
30268986	Ethernet Interface Kit					
30268987	Stacking & Storage Cover (6 pcs)					
30268988	Stacking & Storage Cover (1 pc)					
30045641	Printer, Impact, SF40A					
30472063	Auxiliary display, AD7-MD					
80850043	Security Device					
30269020	Top Loading Kit for Density Determination					
30269021	Carrying Case					
30269022	In-use Cover					



Scout SPX Overload Protection

Model	SPX123	SPX223	SPX222	SPX421	SPX422	SPX621	SPX622	SPX1202	SPX2201	SPX2202	SPX6201	SPX8200	
Capacity (g)	120	220		420		620		1200	2200		6200	8200	
Readability (g)	0.001		0.01	0.1	0.01	0.1	0	.01	0.1	0.01	0.1	1	
Linearity (g)	0.003		0.01	0.1	0.01	0.1	0.02	0.03	0.1	0.03	0.2	1	
Stabilization Time (s)	1.5	1.5	1	1	1	į į	1	1.5	1	1.5	1	4	
Construction	ABS housing and stainless steel pan												
Power Requirement		AC adapter (included) or 4 AA batteries (not included)											
Pan Size (W × D) (mm)	Ø 93 Ø 120 170 × 140 Ø 120 170 × 140												